


YHTEYSHENKILÖMME:


Mikko Nikola 0400-808 718

mikko.nikola@mkoskela.fi



EPÄKESKOPRÄSSIT






C-Framed Models PE30H PE45M PE63AM PE80AM

| Technical data | | PE30H | PE45M | PE63AM | PE80AM |
|---|--------|----------------|----------------|----------------|----------------|
| Nominal press force | kN | 300 | 450 | 630 | 800 |
| Stroke length | mm | 6+60 | 6+90 | 8+100 | 8+120 |
| Slide adjustment | mm | 50 | 50 | 80 | 90 |
| Nominal number of strokes per minute | min -1 | 145 | 130 | 100 | 80 |
| Adjustable strokes per minute (frequency inverter for motor speed variation) | min -1 | option | option | option | option |
| Shut height (distance table-slide) - Distance b/n table&slide, when in BDC, max stroke length and adjustment UP | mm | 270 | 290 | 350 | 350 |
| Throat depth (C-frame depth) | mm | 170 | 205 | 280 | 280 |
| Distance between uprights | mm | 210 | 240 | 350 | 330 |
| Table dimensions | mm | 550x310 | 700x400 | 900x560 | 1000x600 |
| Table hole diameter | mm | dia.125 | dia.165 | dia.250 | dia.250 |
| Slide dimensions | mm | 280x250 | 320x320 | 450x340 | 550x440 |
| Slide guides | pcs | 6 | 6 | 6 | 6 |
| Slide hole diameter | mm | dia.32H7 | dia.40H7 | dia.50H7 | dia.50H7 |
| Table operating height | mm | 780 | 790 | 800 | 800 |
| Motor power | kW | 2,2 | 5,5 | 5,5 | 5,5 |
| Auxillary motor for slide height adjustment | kW | NA | NA | NA | NA |
| Max. pressure in pneumatic system | bar | 6 | 6 | 6 | 6 |
| Overall dimensions (LxWxH) | mm | 1160x1460x2160 | 1125x1280x2325 | 1400x1390x2840 | 1400x1450x2940 |
| Weight | Kg | 2200 | 2850 | 4600 | 6000 |
| Standard Equipment and Options (against payment): | | | | | |
| Manual stroke adjustment | | YES | YES | YES | YES |
| Manual slide adjustment | | YES | YES | YES | YES |
| Motorized slide adjustment | | option | option | option | option |
| Mechanical overload safety device | | YES | YES | YES | YES |
| Hydraulic overload safety device (man.discharge) | | NO | NO | option | option |
| Hydraulic overload safety device (aut.discharge) | | NO | NO | option | option |
| Gear (helical) | | NO | NO | YES | YES |
| Automatic lubrication | | YES | YES | YES | YES |
| Balancing cylinders | | NO | NO | YES | YES |
| Two hands control unit | | YES | YES | YES | YES |
| Pedal | | option | option | option | option |
| Stroke counter | | YES | YES | YES | YES |
| Mechanical barrier guard | | YES | YES | YES | YES |
| Photocell barrier guard | | option | option | option | option |
| Bolster plate and plug | | option | option | option | option |
| Frequency inverter for speed variation | | option | option | option | option |
| Touch screen | | option | option | option | option |
| Die cushion | | option | option | option | option |
| Anti-vibration pads | | option | option | option | option |





Double column

The eccentric presses from the list of VEDI International Ltd. are designed for machining work pieces under power from 25 to 250 tons. High quality of the components, reliable security systems, modern design, easy operation and maintenance, are the main characteristics of the machines. Choosing whichever of the presses you always choose quality, which we guarantee.



Kysy suurempia malleja PE- 250C PE 315C PE 400

VALIKOIMAAN KUULUVAT MYÖS DOBLE COLUMN PRÄSSIT. KYSY!